

Belt : FA2PC

Construction



Top Cover

Material : P/C
 Color : Natural
 Profile : Text.
 Thickness : -
 Hardness - ShA : -



Bottom Cover

Material : P/C
 Color : Natural
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 2
 Fabric Material : P/C
 Lateral Rigidity (Weft) : Flexible
 Internal Material : PU

Working Characteristics

Overall Thickness : 0,06
 Working Load - lbs/in : 57


Overall Weight - lbs/ft² : 0,26
 % Of Elongation : 1,5

Working Temperature (°F) : -13 / 230

Coefficient of friction - Bottom

-On Steel 0,21
 -On Plastic 0,27
 -On Rollers 0,05

Minimum Diameter (F) 0,39"
 Minimum Diameter (C) 0,39"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 1
 Clipper® Lacing 36SP
 Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R
 Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice EZD
 Cooking Temperature (°F) On Demand
 Pressure (lbs) On Demand

Cold Splice ESD
 Glue To Use On Demand

Other Specifications

FDA	Yes	Antistatic	No	Antimicrobial	No
-----	-----	------------	----	---------------	----