


**Belt : 28-44**

**Construction**



Top Cover

Material : Teflon  
 Color : Black  
 Profile : Perf.  
 Thickness : -  
 Hardness - ShA : -



Bottom Cover

Material : Teflon  
 Color : Black  
 Profile : Perf.  
 Thickness : -  
 Hardness - ShA : -

Plies / Weaving

Number of plies : 1  
 Fabric Material : Fiberglass  
 Lateral Rigidity (Weft) : Flexible  
 Internal Material : -

**Working Characteristics**

Overall Thickness : 0  
 Working Load - lbs/in : 0


Overall Weight - lbs/ft<sup>2</sup> : 0  
 % Of Elongation : 0

Working Temperature (°F) : /

Coefficient of friction - Bottom

-On Steel 0  
 -On Plastic 0  
 -On Rollers 0,05

Minimum Diameter (F) -  
 Minimum Diameter (C) -



F = Flexing  
 C = Back Flexing

**Recommended Joint : Metallic**

Alligator® Lacing 1  
 Clipper® Lacing 25  
 Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R  
 Rivet Hinged Fasteners N/R

**Recommended Joint : Endless**

Hot Splice N/R  
 Cooking Temperature (°F) On Demand  
 Pressure (lbs) On Demand

Cold Splice N/R  
 Glue To Use N/R

**Other Specifications**

FDA Yes Antistatic No Antimicrobial No