



**Belt : 2M2964A16A2**

**Construction**



Top Cover

Material : PU  
Color : White  
Profile : Grip  
Thickness : 0,05  
Hardness - ShA : 93



Bottom Cover

Material : PU  
Color : White  
Profile : MRT  
Thickness : 0,02  
Hardness - ShA : 93

Plies / Weaving

Number of plies : 2  
Fabric Material : Polyester  
Lateral Rigidity (Weft) : Rigid  
Internal Material : PU

**Working Characteristics**

Overall Thickness : 0,116  
Working Load - lbs/in : 80


Overall Weight - lbs/ft<sup>2</sup> : 0,5  
% Of Elongation : 1

Working Temperature (°F) : 14 / 176

Coefficient of friction - Bottom

-On Steel 0,35  
-On Plastic 0,3  
-On Rollers 0,05

Minimum Diameter (F) 1,5"  
Minimum Diameter (C) 1,5"



F = Flexing  
C = Back Flexing

**Recommended Joint : Metallic**

Alligator® Lacing 1  
Clipper® Lacing 36SP  
Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R  
Rivet Hinged Fasteners N/R

**Recommended Joint : Endless**

Hot Splice EZ  
Cooking Temperature (°F) On Demand  
Pressure (lbs) On Demand

Cold Splice N/R  
Glue To Use N/R

**Other Specifications**

FDA Yes Antistatic Yes Antimicrobial No