

## Belt : **B1200CT**

### Construction



Top Cover

Material : PVC  
Color : Black  
Profile : CT  
Thickness : 0,175  
Hardness - ShA : 80



Bottom Cover

Material : Polyester  
Color : Black  
Profile : Text.  
Thickness : -  
Hardness - ShA : -

Plies / Weaving

Number of plies : 1  
Fabric Material : Polyester  
Lateral Rigidity (Weft) : Flexible  
Internal Material : PVC

### Working Characteristics

Overall Thickness : 0,24  
Working Load - lbs/in : 120


Overall Weight - lbs/ft<sup>2</sup> : 0,85  
% Of Elongation : 1,5

Working Temperature (°F) : -20 / 176

Coefficient of friction - Bottom

-On Steel 0,8  
-On Plastic 0,2  
-On Rollers 0,05

Minimum Diameter (F) 2"  
Minimum Diameter (C) 2"



F = Flexing  
C = Back Flexing

### Recommended Joint : Metallic

Alligator® Lacing 15  
Clipper® Lacing 1  
Ready Set™ Fasteners 125

Bolt Hinged Fasteners N/R  
Rivet Hinged Fasteners 2

### Recommended Joint : Endless

Hot Splice EZ  
Cooking Temperature (°F) On Demand  
Pressure (lbs) On Demand

Cold Splice ESD  
Glue To Use On Demand

### Other Specifications

|     |    |            |    |               |    |
|-----|----|------------|----|---------------|----|
| FDA | No | Antistatic | No | Antimicrobial | No |
|-----|----|------------|----|---------------|----|