



Belt : B1200RT

Construction



Top Cover

Material : PVC
 Color : Black
 Profile : RT
 Thickness : 0,16
 Hardness - ShA : 80



Bottom Cover

Material : Polyester
 Color : Black
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 1
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Flexible
 Internal Material : PVC

Working Characteristics

Overall Thickness : 0,25
 Working Load - lbs/in : 120


Overall Weight - lbs/ft² : 1
 % Of Elongation : 1,5

Working Temperature (°F) : 2 / 176

Coefficient of friction - Bottom

-On Steel : 0,8
 -On Plastic : 0,2
 -On Rollers : 0,05

Minimum Diameter (F) : 3"
 Minimum Diameter (C) : 3"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 15
 Clipper® Lacing : 1
 Ready Set™ Fasteners : 125

Bolt Hinged Fasteners : 375
 Rivet Hinged Fasteners : 2

Recommended Joint : Endless

Hot Splice : EZ
 Cooking Temperature (°F) : On Demand
 Pressure (lbs) : On Demand

Cold Splice : ESD
 Glue To Use : On Demand

Other Specifications

FDA : No Antistatic : No Antimicrobial : No