


Belt : B2014

Construction



Top Cover

Material : PU
Color : Trans.
Profile : Smooth
Thickness : 0,02
Hardness - ShA : 86



Bottom Cover

Material : Polyester
Color : Natural
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 2
Fabric Material : Polyester
Lateral Rigidity (Weft) : Rigid
Internal Material : PVC

Working Characteristics

Overall Thickness : 0,09
Working Load - lbs/in : 99


Overall Weight - lbs/ft² : 0,53
% Of Elongation : 1

Working Temperature (°F) : 14 / 176

Coefficient of friction - Bottom

-On Steel 0,22
-On Plastic 0,17
-On Rollers 0,05

Minimum Diameter (F) 2,3"
Minimum Diameter (C) 2,3"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 1
Clipper® Lacing 36
Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R
Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice EZZ
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice ESD
Glue To Use On Demand

Other Specifications

FDA Yes Antistatic Yes Antimicrobial No