



Belt : B22CF

Construction



Top Cover

Material : PVC
 Color : Green
 Profile : Smooth
 Thickness : 0,08
 Hardness - ShA : 82



Bottom Cover

Material : Polyester
 Color : Natural
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 2
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Rigid
 Internal Material : PVC

Working Characteristics

Overall Thickness : 0,16
 Working Load - lbs/in : 97


Overall Weight - lbs/ft² : 0,98
 % Of Elongation : 1

Working Temperature (°F) : 23 / 176

Coefficient of friction - Bottom

-On Steel 0,17
 -On Plastic 0,14
 -On Rollers 0,05

Minimum Diameter (F) 3,15"
 Minimum Diameter (C) 3,15"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 15
 Clipper® Lacing 1
 Ready Set™ Fasteners 125

Bolt Hinged Fasteners 375
 Rivet Hinged Fasteners 2

Recommended Joint : Endless

Hot Splice EZZ
 Cooking Temperature (°F) On Demand
 Pressure (lbs) On Demand

Cold Splice ESD
 Glue To Use On Demand

Other Specifications

FDA No Antistatic Yes Antimicrobial No