


**Belt : B2500CBS**

**Construction**



Top Cover

Material : PVC  
 Color : Black  
 Profile : Smooth  
 Thickness : 0,05  
 Hardness - ShA : 80



Bottom Cover

Material : PVC  
 Color : Black  
 Profile : Smooth  
 Thickness : 0,05  
 Hardness - ShA : 80

Plies / Weaving

Number of plies : 1  
 Fabric Material : Polyester  
 Lateral Rigidity (Weft) : Flexible  
 Internal Material : PVC

**Working Characteristics**

Overall Thickness : 0,25  
 Working Load - lbs/in : 250


Overall Weight - lbs/ft<sup>2</sup> : 1,5  
 % Of Elongation : 1

Working Temperature (°F) : 2 / 176

Coefficient of friction - Bottom

-On Steel : 0,4  
 -On Plastic : 0,4  
 -On Rollers : 0,05

Minimum Diameter (F) : 7"  
 Minimum Diameter (C) : 7"



F = Flexing  
 C = Back Flexing

**Recommended Joint : Metallic**

Alligator® Lacing : 27  
 Clipper® Lacing : 4  
 Ready Set™ Fasteners : 187

Bolt Hinged Fasteners : 375  
 Rivet Hinged Fasteners : 5

**Recommended Joint : Endless**

Hot Splice : EZ  
 Cooking Temperature (°F) : On Demand  
 Pressure (lbs) : On Demand

Cold Splice : ESD  
 Glue To Use : On Demand

**Other Specifications**

FDA : No      Antistatic : No      Antimicrobial : No