

Belt : **B4500CBS**

Construction



Top Cover

Material : PVC
Color : Black
Profile : Smooth
Thickness : 0,05
Hardness - ShA : 80



Bottom Cover

Material : PVC
Color : Black
Profile : Smooth
Thickness : 0,05
Hardness - ShA : 80

Plies / Weaving

Number of plies : 1
Fabric Material : Polyester
Lateral Rigidity (Weft) : Flexible
Internal Material : PVC

Working Characteristics

Overall Thickness : 0,37
Working Load - lbs/in : 450


Overall Weight - lbs/ft² : 2,4
% Of Elongation : 1

Working Temperature (°F) : 2 / 176

Coefficient of friction - Bottom

-On Steel 0,83
-On Plastic 0,83
-On Rollers 0,05

Minimum Diameter (F) 10"
Minimum Diameter (C) 10"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 55
Clipper® Lacing 7
Ready Set™ Fasteners N/R

Bolt Hinged Fasteners 550
Rivet Hinged Fasteners 5

Recommended Joint : Endless

Hot Splice EZ
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice ESD
Glue To Use On Demand

Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----