



Belt : F19CK

Construction



Top Cover

Material : PVC
 Color : Blue
 Profile : Smooth
 Thickness : 0,04
 Hardness - ShA : 84



Bottom Cover

Material : PVC
 Color : Blue
 Profile : IP
 Thickness : 0,03
 Hardness - ShA : 90

Plies / Weaving

Number of plies : 2
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Flexible
 Internal Material : PVC

Working Characteristics

Overall Thickness : 0,12
 Working Load - lbs/in : 114


Overall Weight - lbs/ft² : 0,74
 % Of Elongation : 1

Working Temperature (°F) : -13 / 212

Coefficient of friction - Bottom

-On Steel : 0,29
 -On Plastic : 0,33
 -On Rollers : 0,05

Minimum Diameter (F) : 2,95"
 Minimum Diameter (C) : 2,95"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 15
 Clipper® Lacing : 1
 Ready Set™ Fasteners : 125

Bolt Hinged Fasteners : N/R
 Rivet Hinged Fasteners : N/R

Recommended Joint : Endless

Hot Splice : EZZ
 Cooking Temperature (°F) : On Demand
 Pressure (lbs) : On Demand

Cold Splice : ESD
 Glue To Use : On Demand

Other Specifications

FDA : Yes Antistatic : No Antimicrobial : No