


Belt : FC-2UF

Construction



Top Cover

Material : PU
 Color : White
 Profile : Smooth
 Thickness : 0,016
 Hardness - ShA : 83



Bottom Cover

Material : Polyester
 Color : White
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 2
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Flexible
 Internal Material : PU

Working Characteristics

Overall Thickness : 0,063
 Working Load - lbs/in : 57


Overall Weight - lbs/ft² : 0,35
 % Of Elongation : 1

Working Temperature (°F) : -22 / 176

Coefficient of friction - Bottom

-On Steel 0,3
 -On Plastic 0,2
 -On Rollers 0,05

Minimum Diameter (F) 0,2"
 Minimum Diameter (C) 0,2"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 00
 Clipper® Lacing 25
 Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R
 Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice EZ
 Cooking Temperature (°F) On Demand
 Pressure (lbs) On Demand

Cold Splice ESD
 Glue To Use On Demand

Other Specifications

FDA Yes Antistatic No Antimicrobial No