

Belt : *FELW-1.6*

Construction



Top Cover

Material : PU
Color : Blue
Profile : Smooth
Thickness : -
Hardness - ShA : 80



Bottom Cover

Material : PU
Color : Blue
Profile : Text.
Thickness : -
Hardness - ShA : 80

Plies / Weaving

Number of plies : 0
Fabric Material : -
Lateral Rigidity (Weft) : Flexible
Internal Material : PU

Working Characteristics

Overall Thickness : 0,063
Working Load - lbs/in : 2,9


Overall Weight - lbs/ft² : -
% Of Elongation : -

Working Temperature (°F) : -40 / 120

Coefficient of friction - Bottom

-On Steel 0,45
-On Plastic -
-On Rollers 0,05

Minimum Diameter (F) 0,375"
Minimum Diameter (C) 0,375"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 1
Clipper® Lacing 36XSP
Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R
Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice EZ
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice N/R
Glue To Use N/R

Other Specifications

FDA	Yes	Antistatic	No	Antimicrobial	No
-----	-----	------------	----	---------------	----