

Belt : FMB-2

Construction



Top Cover

Material :	PU
Color :	Blue
Profile :	Smooth
Thickness :	-
Hardness - ShA :	95



Bottom Cover

Material :	PU
Color :	Blue
Profile :	Smooth
Thickness :	-
Hardness - ShA :	95


Plies / Weaving

Number of plies :	0
Fabric Material :	-
Lateral Rigidity (Weft) :	Flexible
Internal Material :	PU

Working Characteristics

Overall Thickness :	0,08	Overall Weight - lbs/ft ² :	0,52	Working Temperature (°F) :	-20 / 140
Working Load - lbs/in :	45	% Of Elongation :	-	<u>Coefficient of friction - Bottom</u>	
				-On Steel	0,36
				-On Plastic	-
				-On Rollers	0,05

Minimum Diameter (F)	1,1875"
Minimum Diameter (C)	1,1875"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing	7	Bolt Hinged Fasteners	N/R
Clipper® Lacing	1SP	Rivet Hinged Fasteners	N/R
Ready Set™ Fasteners	62		

Recommended Joint : Endless

Hot Splice	EBD	Cold Splice	N/R
Cooking Temperature (°F)	On Demand	Glue To Use	N/R
Pressure (lbs)	On Demand		

Other Specifications

FDA	Yes	Antistatic	No	Antimicrobial	No
-----	-----	------------	----	---------------	----