


Belt : *FMB-3-MC*

Construction



Top Cover

Material :	PU
Color :	Blue
Profile :	MP
Thickness :	-
Hardness - ShA :	95

Bottom Cover

Material :	PU
Color :	Blue
Profile :	Smooth
Thickness :	-
Hardness - ShA :	95

Plies / Weaving

Number of plies :	0
Fabric Material :	-
Lateral Rigidity (Weft) :	Flexible
Internal Material :	PU

Working Characteristics

Overall Thickness :	0,118
Working Load - lbs/in :	-


Overall Weight - lbs/ft ² :	-
% Of Elongation :	-

Working Temperature (°F) :	-20 / 140
----------------------------	-----------

Coefficient of friction - Bottom

-On Steel	0,36
-On Plastic	-
-On Rollers	0,05

Minimum Diameter (F)	-"
Minimum Diameter (C)	-"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing	15	Bolt Hinged Fasteners	N/R
Clipper® Lacing	1	Rivet Hinged Fasteners	N/R
Ready Set™ Fasteners	125		

Recommended Joint : Endless

Hot Splice	EB	Cold Splice	N/R
Cooking Temperature (°F)	On Demand	Glue To Use	N/R
Pressure (lbs)	On Demand		

Other Specifications

FDA	Yes	Antistatic	No	Antimicrobial	No
-----	-----	------------	----	---------------	----