

**Belt : FMB-3-SD**

**Construction**



Top Cover

Material :	PU
Color :	Blue
Profile :	Smooth
Thickness :	-
Hardness - ShA :	95

Bottom Cover

Material :	PU
Color :	Blue
Profile :	Smooth
Thickness :	-
Hardness - ShA :	95


Plies / Weaving

Number of plies :	0
Fabric Material :	-
Lateral Rigidity (Weft) :	Flexible
Internal Material :	PU

**Working Characteristics**

Overall Thickness :	0,118	Overall Weight - lbs/ft <sup>2</sup> :	-	Working Temperature (°F) :	-20 / 140
Working Load - lbs/in :	-	% Of Elongation :	-	<u>Coefficient of friction - Bottom</u>	
				-On Steel	0,36
				-On Plastic	-
				-On Rollers	0,05

Minimum Diameter (F)	-"
Minimum Diameter (C)	-"



F = Flexing  
C = Back Flexing

**Recommended Joint : Metallic**

Alligator® Lacing	15	Bolt Hinged Fasteners	N/R
Clipper® Lacing	1	Rivet Hinged Fasteners	N/R
Ready Set™ Fasteners	125		

**Recommended Joint : Endless**

Hot Splice	EB	Cold Splice	N/R
Cooking Temperature (°F)	On Demand	Glue To Use	N/R
Pressure (lbs)	On Demand		

**Other Specifications**

FDA	Yes	Antistatic	No	Antimicrobial	No
-----	-----	------------	----	---------------	----