




**TRANSFORCE  
BELTAL** INC.  
COURROIES DE CONVOYEURS | CONVEYOR BELTING

**Belt : PF1200COS**

## Construction



Top Cover

Material : HPVC  
Color : Blue  
Profile : Smooth  
Thickness : 0,05  
Hardness - ShA : 80



Bottom Cover

Material : Polyester  
Color : Blue  
Profile : Text.  
Thickness : -  
Hardness - ShA : -

Plies / Weaving

Number of plies : 1  
Fabric Material : Polyester  
Lateral Rigidity (Weft) : Flexible  
Internal Material : PVC

## Working Characteristics

Overall Thickness : 0,132  
Working Load - lbs/in : 120


Overall Weight - lbs/ft<sup>2</sup> : 0,85  
% Of Elongation : 1,5

Working Temperature (°F) : -40 / 176

### Coefficient of friction - Bottom

-On Steel 0,4  
-On Plastic 0,3  
-On Rollers 0,05

Minimum Diameter (F) 2"  
Minimum Diameter (C) 3"



F = Flexing  
C = Back Flexing

## Recommended Joint : Metallic

Alligator® Lacing 15  
Clipper® Lacing 1  
Ready Set™ Fasteners 125

Bolt Hinged Fasteners N/R  
Rivet Hinged Fasteners 2

## Recommended Joint : Endless

Hot Splice EZ  
Cooking Temperature (°F) On Demand  
Pressure (lbs) On Demand

Cold Splice ESD  
Glue To Use On Demand

## Other Specifications

FDA No Antistatic No Antimicrobial No