


**Belt : FMW-2**

**Construction**



Top Cover

Material : PU  
Color : Beige  
Profile : Smooth  
Thickness : -  
Hardness - ShA : 95



Bottom Cover

Material : PU  
Color : Beige  
Profile : Smooth  
Thickness : -  
Hardness - ShA : 95

Plies / Weaving

Number of plies : 0  
Fabric Material : -  
Lateral Rigidity (Weft) : Flexible  
Internal Material : PU

**Working Characteristics**

Overall Thickness : 0,08  
Working Load - lbs/in : 45


Overall Weight - lbs/ft<sup>2</sup> : 0,53  
% Of Elongation : -

Working Temperature (°F) : -20 / 140

Coefficient of friction - Bottom

-On Steel 0,36  
-On Plastic -  
-On Rollers 0,05

Minimum Diameter (F) 1,1875"  
Minimum Diameter (C) 1,1875"



F = Flexing  
C = Back Flexing

**Recommended Joint : Metallic**

Alligator® Lacing 7  
Clipper® Lacing 1XSP  
Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R  
Rivet Hinged Fasteners N/R

**Recommended Joint : Endless**

Hot Splice EB  
Cooking Temperature (°F) On Demand  
Pressure (lbs) On Demand

Cold Splice N/R  
Glue To Use N/R

**Other Specifications**

FDA Yes Antistatic No Antimicrobial No