


Belt : **FP01-3**

Construction



Top Cover

Material : **NBR**
 Color : **White**
 Profile : **Smooth**
 Thickness : **0,047**
 Hardness - ShA : **70**



Bottom Cover

Material : **Polyester**
 Color : **White**
 Profile : **-**
 Thickness : **-**
 Hardness - ShA : **-**

Plies / Weaving

Number of plies : **3**
 Fabric Material : **Polyester**
 Lateral Rigidity (Weft) : **Flexible**
 Internal Material : **NBR**

Working Characteristics

Overall Thickness : **0,124**
 Working Load - lbs/in : **105**


Overall Weight - lbs/ft² : **0,75**
 % Of Elongation : **1**

Working Temperature (°F) : **0 / 250**

Coefficient of friction - Bottom

-On Steel **0,3**
 -On Plastic **0,3**
 -On Rollers **0,05**

Minimum Diameter (F) **2,5"**
 Minimum Diameter (C) **4"**



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing **15**
 Clipper® Lacing **1**
 Ready Set™ Fasteners **125**

Bolt Hinged Fasteners **N/R**
 Rivet Hinged Fasteners **N/R**

Recommended Joint : Endless

Hot Splice **ESD**
 Cooking Temperature (°F) **On Demand**
 Pressure (lbs) **On Demand**

Cold Splice **ESD**
 Glue To Use **On Demand**

Other Specifications

FDA **Yes** Antistatic **No** Antimicrobial **No**