



Belt : **FP02-3**

Construction



Top Cover



Bottom Cover

Plies / Weaving

Material : **NBR**
Color : **Black**
Profile : **Smooth**
Thickness : **0,047**
Hardness - ShA : **70**

Material : **P/C**
Color : **Black**
Profile : **-**
Thickness : **-**
Hardness - ShA : **-**

Number of plies : **3**
Fabric Material : **P/C**
Lateral Rigidity (Weft) : **Flexible**
Internal Material : **NBR**

Working Characteristics

Overall Thickness : **0,124**
Working Load - lbs/in : **50**


Overall Weight - lbs/ft² : **0,75**
% Of Elongation : **1,5**

Working Temperature (°F) : **0 / 250**

Coefficient of friction - Bottom

-On Steel **0,4**
-On Plastic **0,3**
-On Rollers **0,05**

Minimum Diameter (F) **2"**
Minimum Diameter (C) **2"**



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing **15**
Clipper® Lacing **1**
Ready Set™ Fasteners **125**

Bolt Hinged Fasteners **N/R**
Rivet Hinged Fasteners **N/R**

Recommended Joint : Endless

Hot Splice **ESD**
Cooking Temperature (°F) **On Demand**
Pressure (lbs) **On Demand**

Cold Splice **ESD**
Glue To Use **On Demand**

Other Specifications

FDA **No** Antistatic **No** Antimicrobial **No**