



**Belt : FP06-3**

**Construction**



Top Cover

Material : NBR  
Color : White  
Profile : MRT  
Thickness : 0,047  
Hardness - Sha : 70



Bottom Cover

Material : Polyester  
Color : White  
Profile : -  
Thickness : -  
Hardness - Sha : -

Plies / Weaving

Number of plies : 3  
Fabric Material : Polyester  
Lateral Rigidity (Weft) : Flexible  
Internal Material : NBR

**Working Characteristics**

Overall Thickness : 0,132  
Working Load - lbs/in : 105


Overall Weight - lbs/ft<sup>2</sup> : 0,76  
% Of Elongation : 1

Working Temperature (°F) : 0 / 250

Coefficient of friction - Bottom

-On Steel : 0,3  
-On Plastic : 0,3  
-On Rollers : 0,05

Minimum Diameter (F) : 2,5"  
Minimum Diameter (C) : 2,5"



F = Flexing  
C = Back Flexing

**Recommended Joint : Metallic**

Alligator® Lacing : 15  
Clipper® Lacing : 1  
Ready Set™ Fasteners : 125

Bolt Hinged Fasteners : N/R  
Rivet Hinged Fasteners : N/R

**Recommended Joint : Endless**

Hot Splice : ESD  
Cooking Temperature (°F) : On Demand  
Pressure (lbs) : On Demand

Cold Splice : ESD  
Glue To Use : On Demand

**Other Specifications**

FDA : Yes      Antistatic : No      Antimicrobial : No