



Belt : **FP09-3G**

Construction



Top Cover

Material : NAT
Color : Beige
Profile : RT
Thickness : 0,175
Hardness - ShA : 40



Bottom Cover

Material : Polyester
Color : Brown
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 3
Fabric Material : Polyester
Lateral Rigidity (Weft) : Flexible
Internal Material : NAT

Working Characteristics

Overall Thickness : 0,297
Working Load - lbs/in : 240


Overall Weight - lbs/ft² : 1,34
% Of Elongation : 2

Working Temperature (°F) : -20 / 225

Coefficient of friction - Bottom

-On Steel 0,22
-On Plastic 0,2
-On Rollers 0,05

Minimum Diameter (F) 4"
Minimum Diameter (C) 4"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 15
Clipper® Lacing 1
Ready Set™ Fasteners 125

Bolt Hinged Fasteners 375
Rivet Hinged Fasteners 2

Recommended Joint : Endless

Hot Splice ESD
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice ESD
Glue To Use On Demand

Other Specifications

FDA No Antistatic No Antimicrobial No