


Belt : **FP10-3**

Construction



Top Cover

Material : BUTYL
Color : White
Profile : Smooth
Thickness : 0,031
Hardness - ShA : 70



Bottom Cover

Material : Polyester
Color : White
Profile : -
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 3
Fabric Material : Polyester
Lateral Rigidity (Weft) : Flexible
Internal Material : BUTYL

Working Characteristics

Overall Thickness : 0,103
Working Load - lbs/in : 105


Overall Weight - lbs/ft² : 0,67
% Of Elongation : 1

Working Temperature (°F) : -65 / 300

Coefficient of friction - Bottom

-On Steel 0,4
-On Plastic 0,3
-On Rollers 0,05

Minimum Diameter (F) 2,5"
Minimum Diameter (C) 2,5"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 15
Clipper® Lacing 1
Ready Set™ Fasteners 125

Bolt Hinged Fasteners N/R
Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice ESD
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice ESD
Glue To Use On Demand

Other Specifications

FDA	Yes	Antistatic	No	Antimicrobial	No
-----	-----	------------	----	---------------	----