

Belt : FP11-2B

Construction



Top Cover

Material : PU
Color : Blue
Profile : Smooth
Thickness : 0,016
Hardness - ShA : 92



Bottom Cover

Material : Polyester
Color : White
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 2
Fabric Material : Polyester
Lateral Rigidity (Weft) : Rigid
Internal Material : PU

Working Characteristics

Overall Thickness : 0,051
Working Load - lbs/in : 40


Overall Weight - lbs/ft² : 0,29
% Of Elongation : 1

Working Temperature (°F) : -4 / 212

Coefficient of friction - Bottom

-On Steel : 0,15
-On Plastic : -
-On Rollers : 0,05

Minimum Diameter (F) : 1"
Minimum Diameter (C) : 1"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 00
Clipper® Lacing : 36XSP
Ready Set™ Fasteners : 62

Bolt Hinged Fasteners : N/R
Rivet Hinged Fasteners : N/R

Recommended Joint : Endless

Hot Splice : EZ
Cooking Temperature (°F) : On Demand
Pressure (lbs) : On Demand

Cold Splice : ESD
Glue To Use : On Demand

Other Specifications

FDA : Yes Antistatic : Yes Antimicrobial : Yes