


Belt : **FP11-2NF**

Construction



Top Cover

Material : PU
Color : White
Profile : Smooth
Thickness : 0,016
Hardness - ShA : 92



Bottom Cover

Material : Polyester
Color : White
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 2
Fabric Material : Polyester
Lateral Rigidity (Weft) : Rigid
Internal Material : PU

Working Characteristics

Overall Thickness : 0,051
Working Load - lbs/in : 40


Overall Weight - lbs/ft² : 0,31
% Of Elongation : 1

Working Temperature (°F) : -4 / 212

Coefficient of friction - Bottom

-On Steel 0,15
-On Plastic 0,2
-On Rollers 0,05

Minimum Diameter (F) 0,47"
Minimum Diameter (C) 0,47"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 00
Clipper® Lacing 36XSP
Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R
Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice EZ
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice N/R
Glue To Use N/R

Other Specifications

FDA	Yes	Antistatic	No	Antimicrobial	No
-----	-----	------------	----	---------------	----