


Belt : **FP13-3**

Construction



Top Cover

Material : Teflon
 Color : White
 Profile : Smooth
 Thickness : 0,002
 Hardness - ShA : 90



Bottom Cover

Material : Polyester
 Color : White
 Profile : -
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 3
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Flexible
 Internal Material : NBR

Working Characteristics

Overall Thickness : 0,079
 Working Load - lbs/in : 105


Overall Weight - lbs/ft² : 0,52
 % Of Elongation : 1

Working Temperature (°F) : 0 / 250

Coefficient of friction - Bottom

-On Steel 0,3
 -On Plastic 0,3
 -On Rollers 0,05

Minimum Diameter (F) 2"
 Minimum Diameter (C) 2"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 7
 Clipper® Lacing 1XSP
 Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R
 Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice ESD
 Cooking Temperature (°F) On Demand
 Pressure (lbs) On Demand

Cold Splice ESD
 Glue To Use On Demand

Other Specifications

FDA	Yes	Antistatic	No	Antimicrobial	No
-----	-----	------------	----	---------------	----