

Belt : FP15-3DP

Construction



Top Cover

Material : PVC
 Color : White
 Profile : Smooth
 Thickness : 0,039
 Hardness - ShA : 65



Bottom Cover

Material : Polyester
 Color : White
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 3
 Fabric Material : P/N
 Lateral Rigidity (Weft) : Rigid
 Internal Material : PVC

Working Characteristics

Overall Thickness : 0,189
 Working Load - lbs/in : 86


Overall Weight - lbs/ft² : 1,13
 % Of Elongation : 1

Working Temperature (°F) : 14 / 194

Coefficient of friction - Bottom

-On Steel 0,2
 -On Plastic 0,19
 -On Rollers 0,05

Minimum Diameter (F) 3,9"
 Minimum Diameter (C) 3,9"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 15
 Clipper® Lacing 3
 Ready Set™ Fasteners 125

Bolt Hinged Fasteners N/R
 Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice EZZ
 Cooking Temperature (°F) On Demand
 Pressure (lbs) On Demand

Cold Splice ESD
 Glue To Use On Demand

Other Specifications

FDA Yes Antistatic No Antimicrobial No