


Belt : **FP25-2T**

Construction



Top Cover

Material : NAT
 Color : Beige
 Profile : DIA
 Thickness : 0,22
 Hardness - ShA : 40



Bottom Cover

Material : Polyester
 Color : Brown
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 2
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Rigid
 Internal Material : SBR

Working Characteristics

Overall Thickness : 0,324
 Working Load - lbs/in : 150


Overall Weight - lbs/ft² : 1,3
 % Of Elongation : 1

Working Temperature (°F) : -40 / 250

Coefficient of friction - Bottom

-On Steel 0,3
 -On Plastic 0,15
 -On Rollers 0,05

Minimum Diameter (F) 2,5"
 Minimum Diameter (C) 2,5"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 15
 Clipper® Lacing 1
 Ready Set™ Fasteners 125

Bolt Hinged Fasteners N/R
 Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice ESD
 Cooking Temperature (°F) On Demand
 Pressure (lbs) On Demand

Cold Splice ESD
 Glue To Use On Demand

Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----