


Belt : **FP32-2**

Construction



Top Cover



Bottom Cover

Plies / Weaving

Material : PVC
 Color : Grey
 Profile : RIB
 Thickness : 0,066
 Hardness - ShA : 50

Material : Polyester
 Color : Natural
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Number of plies : 2
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Rigid
 Internal Material : PVC

Working Characteristics

Overall Thickness : 0,12
 Working Load - lbs/in : 62


Overall Weight - lbs/ft² : 0,71
 % Of Elongation : 1

Working Temperature (°F) : 14 / 176

Coefficient of friction - Bottom

-On Steel 0,22
 -On Plastic 0,19
 -On Rollers 0,05

Minimum Diameter (F) 1,9"
 Minimum Diameter (C) 1,9"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 7
 Clipper® Lacing 1XSP
 Ready Set™ Fasteners 62

Bolt Hinged Fasteners N/R
 Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice EZZ
 Cooking Temperature (°F) On Demand
 Pressure (lbs) On Demand

Cold Splice ESD
 Glue To Use On Demand

Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----