



Belt : H12Y1R

Construction



Top Cover

Material : HPVC
Color : Green
Profile : Text.
Thickness : 0,02
Hardness - ShA : 75



Bottom Cover

Material : RC
Color : Black
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 2
Fabric Material : Polyester
Lateral Rigidity (Weft) : Rigid
Internal Material : PVC

Working Characteristics

Overall Thickness : 0,08
Working Load - lbs/in : 57


Overall Weight - lbs/ft² : 0,47
% Of Elongation : 1

Working Temperature (°F) : 23 / 176

Coefficient of friction - Bottom

-On Steel : 0,13
-On Plastic : 0,12
-On Rollers : 0,05

Minimum Diameter (F) : 0,98"
Minimum Diameter (C) : 0,98"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 7
Clipper® Lacing : 1XSP
Ready Set™ Fasteners : 62

Bolt Hinged Fasteners : N/R
Rivet Hinged Fasteners : N/R

Recommended Joint : Endless

Hot Splice : EZ
Cooking Temperature (°F) : On Demand
Pressure (lbs) : On Demand

Cold Splice : ESD
Glue To Use : On Demand

Other Specifications

FDA : No Antistatic : No Antimicrobial : No