



Belt : **HSW-3**

Construction



Top Cover

Material :	COTTON
Color :	Natural
Profile :	Text.
Thickness :	-
Hardness - ShA :	-



Bottom Cover

Material :	P/C
Color :	Black
Profile :	-
Thickness :	-
Hardness - ShA :	-

Plies / Weaving

Number of plies :	3
Fabric Material :	P/C
Lateral Rigidity (Weft) :	Flexible
Internal Material :	SBR

Working Characteristics

Overall Thickness :	0,141
Working Load - lbs/in :	90


Overall Weight - lbs/ft ² :	0,67
% Of Elongation :	1,5

Working Temperature (*F) :	-40 / 250
----------------------------	-----------

Coefficient of friction - Bottom

-On Steel	0,4
-On Plastic	0,3
-On Rollers	0,05

Minimum Diameter (F)	2,5"
Minimum Diameter (C)	2,5"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing	15
Clipper® Lacing	2
Ready Set™ Fasteners	125

Bolt Hinged Fasteners	N/R
Rivet Hinged Fasteners	N/R

Recommended Joint : Endless

Hot Splice	ESD
Cooking Temperature (*F)	On Demand
Pressure (lbs)	On Demand

Cold Splice	ESD
Glue To Use	On Demand

Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----