


Belt : *HSW-4*

Construction



Top Cover

Material : COTTON
Color : Natural
Profile : Text.
Thickness : -
Hardness - ShA : -

Bottom Cover

Material : P/C
Color : Black
Profile : -
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 4
Fabric Material : P/C
Lateral Rigidity (Weft) : Flexible
Internal Material : SBR

Working Characteristics

Overall Thickness : 0,1875
Working Load - lbs/in : 120


Overall Weight - lbs/ft² : 1,06
% Of Elongation : 1,5

Working Temperature (°F) : -40 / 250

Coefficient of friction - Bottom

-On Steel 0,4
-On Plastic 0,3
-On Rollers 0,05

Minimum Diameter (F) 3"
Minimum Diameter (C) 3"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 25
Clipper® Lacing 3
Ready Set™ Fasteners 187

Bolt Hinged Fasteners N/R
Rivet Hinged Fasteners N/R

Recommended Joint : Endless

Hot Splice ESD
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice ESD
Glue To Use On Demand

Other Specifications

FDA No Antistatic No Antimicrobial No