

Belt : **NP6660**

Construction

Top Cover

Material : PU
Color : White
Profile : Smooth
Thickness : -
Hardness - ShA : -

Bottom Cover

Material : Polyester
Color : White
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 2
Fabric Material : Polyester
Lateral Rigidity (Weft) : Rigid
Internal Material : -

Working Characteristics

Overall Thickness : -
Working Load - lbs/in : -


Overall Weight - lbs/ft² : -
% Of Elongation : -

Working Temperature (°F) : - / -

Coefficient of friction - Bottom

-On Steel : -
-On Plastic : -
-On Rollers : 0,05

Minimum Diameter (F) : -"
Minimum Diameter (C) : -"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 15
Clipper® Lacing : 1
Ready Set™ Fasteners : 62

Bolt Hinged Fasteners : N/R
Rivet Hinged Fasteners : N/R

Recommended Joint : Endless

Hot Splice : EZD
Cooking Temperature (°F) : On Demand
Pressure (lbs) : On Demand

Cold Splice : N/R
Glue To Use : N/R

Other Specifications

FDA : Yes Antistatic : Yes Antimicrobial : No