



Belt : P2220 3/16xBR MOR

Construction



Top Cover

Material : NBR
Color : Black
Profile : Smooth
Thickness : 0,187
Hardness - ShA : 70



Bottom Cover

Material : Polyester
Color : Brown
Profile : Text.
Thickness : -
Hardness - ShA : 0

Plies / Weaving

Number of plies : 2
Fabric Material : P/N
Lateral Rigidity (Weft) : Flexible
Internal Material : NBR

Working Characteristics

Overall Thickness : 0,3
Working Load - lbs/in : 220


Overall Weight - lbs/ft² : 1,98
% Of Elongation : 1

Working Temperature (°F) : -20 / 200

Coefficient of friction - Bottom

-On Steel 0,3
-On Plastic 0,2
-On Rollers 0,05

Minimum Diameter (F) 8"
Minimum Diameter (C) 8"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 35
Clipper® Lacing 2
Ready Set™ Fasteners 187

Bolt Hinged Fasteners 375
Rivet Hinged Fasteners 5

Recommended Joint : Endless

Hot Splice ESD
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice ESD
Glue To Use On Demand

Other Specifications

FDA No Antistatic No Antimicrobial No