


Belt : P2220 3/16x1/16

Construction



Top Cover

Material : SBR
Color : Black
Profile : Smooth
Thickness : 0,187
Hardness - ShA : 70



Bottom Cover

Material : SBR
Color : Black
Profile : Smooth
Thickness : 0,06
Hardness - ShA : 70

Plies / Weaving

Number of plies : 2
Fabric Material : P/N
Lateral Rigidity (Weft) : Flexible
Internal Material : SBR

Working Characteristics

Overall Thickness : 0,36
Working Load - lbs/in : 220


Overall Weight - lbs/ft² : 2,4
% Of Elongation : 1

Working Temperature (°F) : -20 / 250

Coefficient of friction - Bottom

-On Steel : 0,5
-On Plastic : 0,45
-On Rollers : 0,05

Minimum Diameter (F) : 8"
Minimum Diameter (C) : 8"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 45
Clipper® Lacing : 3
Ready Set™ Fasteners : 187

Bolt Hinged Fasteners : 375
Rivet Hinged Fasteners : 5

Recommended Joint : Endless

Hot Splice : ESD
Cooking Temperature (°F) : On Demand
Pressure (lbs) : On Demand

Cold Splice : ESD
Glue To Use : On Demand

Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----