

Belt : P3330 1/16x1/16 - HT

Construction

Top Cover

Material :	EPDM
Color :	Black
Profile :	Smooth
Thickness :	0,062
Hardness - ShA :	70

Bottom Cover

Material :	EPDM
Color :	Black
Profile :	Smooth
Thickness :	0,06
Hardness - ShA :	70

Plies / Weaving

Number of plies :	3
Fabric Material :	P/N
Lateral Rigidity (Weft) :	Flexible
Internal Material :	EPDM


Working Characteristics

Overall Thickness :	0,5	Overall Weight - lbs/ft ² :	3	Working Temperature (°F) :	-25 / 700
Working Load - lbs/in :	330	% Of Elongation :	1		

Coefficient of friction - Bottom

-On Steel	0,5
-On Plastic	0,45
-On Rollers	0,05

Minimum Diameter (F)	14"
Minimum Diameter (C)	14"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing	65	Bolt Hinged Fasteners	550
Clipper® Lacing	4	Rivet Hinged Fasteners	6
Ready Set™ Fasteners	187		

Recommended Joint : Endless

Hot Splice	ESD	Cold Splice	ESD
Cooking Temperature (°F)	On Demand	Glue To Use	On Demand
Pressure (lbs)	On Demand		

Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----