



Belt : P3330 3/16x1/16

Construction



Top Cover

Material : SBR
Color : Black
Profile : Smooth
Thickness : 0,187
Hardness - ShA : 70



Bottom Cover

Material : SBR
Color : Black
Profile : Smooth
Thickness : 0,06
Hardness - ShA : 70

Plies / Weaving

Number of plies : 3
Fabric Material : P/N
Lateral Rigidity (Weft) : Flexible
Internal Material : SBR

Working Characteristics

Overall Thickness : 0,41
Working Load - lbs/in : 330


Overall Weight - lbs/ft² : 2,6
% Of Elongation : 1

Working Temperature (°F) : -20 / 250

Coefficient of friction - Bottom

-On Steel 0,5
-On Plastic 0,45
-On Rollers 0,05

Minimum Diameter (F) 12"
Minimum Diameter (C) 12"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 55
Clipper® Lacing 4
Ready Set™ Fasteners 187

Bolt Hinged Fasteners 550
Rivet Hinged Fasteners 5

Recommended Joint : Endless

Hot Splice ESD
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice ESD
Glue To Use On Demand

Other Specifications

FDA No Antistatic No Antimicrobial No