


Belt : P3330 3/16xBR MOR

Construction



Top Cover

Material :	NBR
Color :	Black
Profile :	Smooth
Thickness :	0,187
Hardness - ShA :	70



Bottom Cover

Material :	Polyester
Color :	Brown
Profile :	Text.
Thickness :	-
Hardness - ShA :	-

Plies / Weaving

Number of plies :	3
Fabric Material :	P/N
Lateral Rigidity (Weft) :	Flexible
Internal Material :	NBR


Working Characteristics

Overall Thickness :	0,35	Overall Weight - lbs/ft ² :	2,1	Working Temperature (°F) :	-20 / 200
Working Load - lbs/in :	330	% Of Elongation :	1		

Coefficient of friction - Bottom

-On Steel	0,3
-On Plastic	0,2
-On Rollers	0,05

Minimum Diameter (F)	10"
Minimum Diameter (C)	10"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing	45	Bolt Hinged Fasteners	375
Clipper® Lacing	3	Rivet Hinged Fasteners	5
Ready Set™ Fasteners	187		

Recommended Joint : Endless

Hot Splice	ESD	Cold Splice	ESD
Cooking Temperature (°F)	On Demand	Glue To Use	On Demand
Pressure (lbs)	On Demand		

Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----