

## Belt : P4440 1/4x1/16

### Construction

#### Top Cover

Material :	SBR
Color :	Black
Profile :	Smooth
Thickness :	0,25
Hardness - ShA :	70

#### Bottom Cover

Material :	SBR
Color :	Black
Profile :	Smooth
Thickness :	0,06
Hardness - ShA :	70

#### Plies / Weaving

Number of plies :	4
Fabric Material :	P/N
Lateral Rigidity (Weft) :	Flexible
Internal Material :	SBR

### Working Characteristics

Overall Thickness :	0,5
Working Load - lbs/in :	440


Overall Weight - lbs/ft <sup>2</sup> :	3,42
% Of Elongation :	0

Working Temperature (*F) :	-20 / 250
----------------------------	-----------

#### Coefficient of friction - Bottom

-On Steel	0
-On Plastic	0
-On Rollers	0,05

Minimum Diameter (F)	18"
Minimum Diameter (C)	18"



F = Flexing  
C = Back Flexing

### Recommended Joint : Metallic

Alligator® Lacing	65
Clipper® Lacing	5
Ready Set™ Fasteners	187

Bolt Hinged Fasteners	550
Rivet Hinged Fasteners	6

### Recommended Joint : Endless

Hot Splice	ESD
Cooking Temperature (*F)	On Demand
Pressure (lbs)	On Demand

Cold Splice	ESD
Glue To Use	On Demand

### Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----