

**Belt : PT1.2 0-U2**

**Construction**

Top Cover

Material : PU  
 Color : Green  
 Profile : Smooth  
 Thickness : 0,008  
 Hardness - ShA : 90

Bottom Cover

Material : PU  
 Color : White  
 Profile : Text.  
 Thickness : -  
 Hardness - ShA : -

Plies / Weaving

Number of plies : 2  
 Fabric Material : Polyester  
 Lateral Rigidity (Weft) : Rigid  
 Internal Material : PU

**Working Characteristics**

Overall Thickness : 0,05  
 Working Load - lbs/in : 34


Overall Weight - lbs/ft<sup>2</sup> : 0,27  
 % Of Elongation : 1

Working Temperature (°F) : -4 / 212

Coefficient of friction - Bottom

-On Steel : 0,2  
 -On Plastic : 0,25  
 -On Rollers : 0,05

Minimum Diameter (F) : 0,8"  
 Minimum Diameter (C) : 0,8"



F = Flexing  
 C = Back Flexing

**Recommended Joint : Metallic**

Alligator® Lacing : 00  
 Clipper® Lacing : 36XSP  
 Ready Set™ Fasteners : N/R

Bolt Hinged Fasteners : N/R  
 Rivet Hinged Fasteners : N/R

**Recommended Joint : Endless**

Hot Splice : EZ  
 Cooking Temperature (°F) : On Demand  
 Pressure (lbs) : On Demand

Cold Splice : N/R  
 Glue To Use : N/R

**Other Specifications**

FDA : No      Antistatic : No      Antimicrobial : No