



Belt : *PYR-2*

Construction



Top Cover

Material : NBR
 Color : White
 Profile : Pyramide
 Thickness : 0,12
 Hardness - ShA : 70



Bottom Cover

Material : Polyester
 Color : White
 Profile : -
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 2
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Flexible
 Internal Material : NBR

Working Characteristics

Overall Thickness : 0,137
 Working Load - lbs/in : 90


Overall Weight - lbs/ft² : 0,66
 % Of Elongation : 1

Working Temperature (°F) : 0 / 250

Coefficient of friction - Bottom

-On Steel : 0,4
 -On Plastic : 0,3
 -On Rollers : 0,05

Minimum Diameter (F) : 2"
 Minimum Diameter (C) : 2"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 7
 Clipper® Lacing : 36
 Ready Set™ Fasteners : 62

Bolt Hinged Fasteners : N/R
 Rivet Hinged Fasteners : N/R

Recommended Joint : Endless

Hot Splice : N/R
 Cooking Temperature (°F) : On Demand
 Pressure (lbs) : On Demand

Cold Splice : ESD
 Glue To Use : On Demand

Other Specifications

FDA : Yes Antistatic : No Antimicrobial : No