


## Belt : *PYR-3*

### Construction



#### Top Cover

Material : NBR  
Color : White  
Profile : Pyramide  
Thickness : 0,12  
Hardness - ShA : 70

#### Bottom Cover

Material : Polyester  
Color : White  
Profile : -  
Thickness : -  
Hardness - ShA : -

#### Plies / Weaving

Number of plies : 3  
Fabric Material : Polyester  
Lateral Rigidity (Weft) : Flexible  
Internal Material : NBR

### Working Characteristics

Overall Thickness : 0,204  
Working Load - lbs/in : 90


Overall Weight - lbs/ft<sup>2</sup> : 1,2  
% Of Elongation : 1

Working Temperature (°F) : 0 / 250

#### Coefficient of friction - Bottom

-On Steel 0,4  
-On Plastic 0,3  
-On Rollers 0,05

Minimum Diameter (F) 2,5"  
Minimum Diameter (C) 2,5"



F = Flexing  
C = Back Flexing

### Recommended Joint : Metallic

Alligator® Lacing 15  
Clipper® Lacing 1  
Ready Set™ Fasteners 125

Bolt Hinged Fasteners N/R  
Rivet Hinged Fasteners N/R

### Recommended Joint : Endless

Hot Splice N/R  
Cooking Temperature (°F) On Demand  
Pressure (lbs) On Demand

Cold Splice ESD  
Glue To Use On Demand

### Other Specifications

|     |     |            |    |               |    |
|-----|-----|------------|----|---------------|----|
| FDA | Yes | Antistatic | No | Antimicrobial | No |
|-----|-----|------------|----|---------------|----|