


Belt : R1200UCOS

Construction



Top Cover

Material : PU
Color : Red
Profile : Smooth
Thickness : 0,08
Hardness - ShA : 90



Bottom Cover

Material : Polyester
Color : Red
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 1
Fabric Material : Polyester
Lateral Rigidity (Weft) : Flexible
Internal Material : PU

Working Characteristics

Overall Thickness : 0,22
Working Load - lbs/in : 120


Overall Weight - lbs/ft² : 1,3
% Of Elongation : 1,5

Working Temperature (°F) : 20 / 180

Coefficient of friction - Bottom

-On Steel : 0,4
-On Plastic : 0,2
-On Rollers : 0,05

Minimum Diameter (F) : 3"
Minimum Diameter (C) : 3"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 20
Clipper® Lacing : 2
Ready Set™ Fasteners : 187

Bolt Hinged Fasteners : 375
Rivet Hinged Fasteners : 2

Recommended Joint : Endless

Hot Splice : EZ
Cooking Temperature (°F) : On Demand
Pressure (lbs) : On Demand

Cold Splice : ESD
Glue To Use : On Demand

Other Specifications

FDA : No Antistatic : No Antimicrobial : No