

Belt : SL-10

Construction

Top Cover

Material : Silicone
 Color : Trans.
 Profile : Smooth
 Thickness : -
 Hardness - ShA : -

Bottom Cover

Material : Polyester
 Color : Natural
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 1
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Flexible
 Internal Material : -

Working Characteristics

Overall Thickness : -
 Working Load - lbs/in : -


Overall Weight - lbs/ft² : -
 % Of Elongation : -

Working Temperature (°F) : - / -

Coefficient of friction - Bottom

-On Steel : -
 -On Plastic : -
 -On Rollers : 0,05

Minimum Diameter (F) : -"
 Minimum Diameter (C) : -"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 00
 Clipper® Lacing : 25
 Ready Set™ Fasteners : N/R

Bolt Hinged Fasteners : N/R
 Rivet Hinged Fasteners : N/R

Recommended Joint : Endless

Hot Splice : EZD
 Cooking Temperature (°F) : On Demand
 Pressure (lbs) : On Demand

Cold Splice : N/R
 Glue To Use : N/R

Other Specifications

FDA : Yes Antistatic : Yes Antimicrobial : No