

Belt : T04/U

Construction



Top Cover

Material : PU
Color : White
Profile : Smooth
Thickness : 0,005
Hardness - ShA : 86

Bottom Cover

Material : Polyester
Color : White
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 1
Fabric Material : Polyester
Lateral Rigidity (Weft) : Rigid
Internal Material : -

Working Characteristics

Overall Thickness : 0,02
Working Load - lbs/in : 17


Overall Weight - lbs/ft² : 0,12
% Of Elongation : 1

Working Temperature (°F) : -22 / 176

Coefficient of friction - Bottom

-On Steel : 0,15
-On Plastic : 0,2
-On Rollers : 0,05

Minimum Diameter (F) : 0,6"
Minimum Diameter (C) : 0,6"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 00
Clipper® Lacing : 36XSP
Ready Set™ Fasteners : N/R

Bolt Hinged Fasteners : N/R
Rivet Hinged Fasteners : N/R

Recommended Joint : Endless

Hot Splice : EZD
Cooking Temperature (°F) : On Demand
Pressure (lbs) : On Demand

Cold Splice : N/R
Glue To Use : N/R

Other Specifications

FDA : Yes Antistatic : No Antimicrobial : No