

Belt : TT162-B

Construction



Top Cover

Material : PU
 Color : Blue
 Profile : Smooth
 Thickness : 0,008
 Hardness - ShA : 85

Bottom Cover

Material : PU
 Color : Blue
 Profile : IP
 Thickness : 0,02
 Hardness - ShA : 85

Plies / Weaving

Number of plies : 2
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Rigid
 Internal Material : PU

Working Characteristics

Overall Thickness : 0,083
 Working Load - lbs/in : 40


Overall Weight - lbs/ft² : 0,47
 % Of Elongation : 1

Working Temperature (°F) : -4 / 212

Coefficient of friction - Bottom

-On Steel : 0,15
 -On Plastic : 0,3
 -On Rollers : 0,05

Minimum Diameter (F) : 1,18"
 Minimum Diameter (C) : 1,18"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 1
 Clipper® Lacing : 36SP
 Ready Set™ Fasteners : 62

Bolt Hinged Fasteners : N/R
 Rivet Hinged Fasteners : N/R

Recommended Joint : Endless

Hot Splice : EZ
 Cooking Temperature (°F) : On Demand
 Pressure (lbs) : On Demand

Cold Splice : ESD
 Glue To Use : On Demand

Other Specifications

FDA : Yes Antistatic : No Antimicrobial : Yes