


Belt : TT20-RP

Construction



Top Cover

Material : PU
 Color : White
 Profile : MRT
 Thickness : 0,016
 Hardness - ShA : 93

Bottom Cover

Material : Polyester
 Color : White
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 2
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Rigid
 Internal Material : PU

Working Characteristics

Overall Thickness : 0,09
 Working Load - lbs/in : 69


Overall Weight - lbs/ft² : 0,39
 % Of Elongation : 1

Working Temperature (°F) : -4 / 212

Coefficient of friction - Bottom

-On Steel : 0,3
 -On Plastic : 0,2
 -On Rollers : 0,05

Minimum Diameter (F) : 0,79"
 Minimum Diameter (C) : 0,79"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 00
 Clipper® Lacing : 36XSP
 Ready Set™ Fasteners : 62

Bolt Hinged Fasteners : N/R
 Rivet Hinged Fasteners : N/R

Recommended Joint : Endless

Hot Splice : EZ
 Cooking Temperature (°F) : On Demand
 Pressure (lbs) : On Demand

Cold Splice : ESD
 Glue To Use : On Demand

Other Specifications

FDA : Yes Antistatic : No Antimicrobial : No