


Belt : ***XH500-4***

Construction



Top Cover

Material : **XNBR**
Color : **Blue**
Profile : **Text.**
Thickness : **-**
Hardness - ShA : **-**



Bottom Cover

Material : **XNBR**
Color : **Blue**
Profile : **Text.**
Thickness : **-**
Hardness - ShA : **-**

Plies / Weaving

Number of plies : **2**
Fabric Material : **Polyester**
Lateral Rigidity (Weft) : **Rigid**
Internal Material : **PA**

Working Characteristics

Overall Thickness : **0,157**
Working Load - lbs/in : **21,7**


Overall Weight - lbs/ft² : **0,89**
% Of Elongation : **1**

Working Temperature (°F) : **-4 / 176**

Coefficient of friction - Bottom

-On Steel **0,7**
-On Plastic **-**
-On Rollers **0,05**

Minimum Diameter (F) **2,36"**
Minimum Diameter (C) **2,36"**



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing **15**
Clipper® Lacing **2**
Ready Set™ Fasteners **125**

Bolt Hinged Fasteners **N/R**
Rivet Hinged Fasteners **N/R**

Recommended Joint : Endless

Hot Splice **ESD**
Cooking Temperature (°F) **On Demand**
Pressure (lbs) **On Demand**

Cold Splice **N/R**
Glue To Use **N/R**

Other Specifications

FDA	No	Antistatic	Yes	Antimicrobial	No
-----	----	------------	-----	---------------	----