

**Belt : XH500-6**

**Construction**



Top Cover

Material : XNBR  
Color : Blue  
Profile : Text.  
Thickness : -  
Hardness - ShA : -



Bottom Cover

Material : XNBR  
Color : Blue  
Profile : Text.  
Thickness : -  
Hardness - ShA : -

Plies / Weaving

Number of plies : 2  
Fabric Material : Polyester  
Lateral Rigidity (Weft) : Rigid  
Internal Material : PA

**Working Characteristics**

Overall Thickness : 0,236  
Working Load - lbs/in : 21,7


Overall Weight - lbs/ft<sup>2</sup> : 1,53  
% Of Elongation : 1

Working Temperature (°F) : -4 / 176

Coefficient of friction - Bottom

-On Steel 0,7  
-On Plastic -  
-On Rollers 0,05

Minimum Diameter (F) 3,15"  
Minimum Diameter (C) 3,15"



F = Flexing  
C = Back Flexing

**Recommended Joint : Metallic**

Alligator® Lacing 27  
Clipper® Lacing 4  
Ready Set™ Fasteners 187

Bolt Hinged Fasteners N/R  
Rivet Hinged Fasteners N/R

**Recommended Joint : Endless**

Hot Splice ESD  
Cooking Temperature (°F) On Demand  
Pressure (lbs) On Demand

Cold Splice N/R  
Glue To Use N/R

**Other Specifications**

FDA No Antistatic Yes Antimicrobial No