

Belt : *I225-3HT*

Construction

Top Cover

Material : EPDM
Color : Black
Profile : Smooth
Thickness : 0,125
Hardness - ShA : 70

Bottom Cover

Material : Polyester
Color : Brown
Profile : Text.
Thickness : -
Hardness - ShA : -

Plies / Weaving

Number of plies : 3
Fabric Material : Polyester
Lateral Rigidity (Weft) : Flexible
Internal Material : EPDM

Working Characteristics

Overall Thickness : 0,25
Working Load - lbs/in : 225


Overall Weight - lbs/ft² : 1,62
% Of Elongation : 1

Working Temperature (°F) : -20 / 400

Coefficient of friction - Bottom

-On Steel 0,3
-On Plastic 0,2
-On Rollers 0,05

Minimum Diameter (F) 8"
Minimum Diameter (C) 8"



F = Flexing
C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing 27
Clipper® Lacing 4
Ready Set™ Fasteners 187

Bolt Hinged Fasteners 375
Rivet Hinged Fasteners 2

Recommended Joint : Endless

Hot Splice ESD
Cooking Temperature (°F) On Demand
Pressure (lbs) On Demand

Cold Splice ESD
Glue To Use On Demand

Other Specifications

FDA	No	Antistatic	No	Antimicrobial	No
-----	----	------------	----	---------------	----