


Belt : I225-3PG5

Construction



Top Cover

Material : NAT
 Color : Beige
 Profile : Smooth
 Thickness : 0,187
 Hardness - ShA : 40

Bottom Cover

Material : Polyester
 Color : Brown
 Profile : Text.
 Thickness : -
 Hardness - ShA : -

Plies / Weaving

Number of plies : 3
 Fabric Material : Polyester
 Lateral Rigidity (Weft) : Flexible
 Internal Material : SBR

Working Characteristics

Overall Thickness : 0,375
 Working Load - lbs/in : 240


Overall Weight - lbs/ft² : 2,3
 % Of Elongation : 1

Working Temperature (°F) : -40 / 160

Coefficient of friction - Bottom

-On Steel : 0,3
 -On Plastic : 0,2
 -On Rollers : 0,05

Minimum Diameter (F) : 6"
 Minimum Diameter (C) : 6"



F = Flexing
 C = Back Flexing

Recommended Joint : Metallic

Alligator® Lacing : 20
 Clipper® Lacing : 2
 Ready Set™ Fasteners : 187

Bolt Hinged Fasteners : 375
 Rivet Hinged Fasteners : 5

Recommended Joint : Endless

Hot Splice : ESD
 Cooking Temperature (°F) : On Demand
 Pressure (lbs) : On Demand

Cold Splice : ESD
 Glue To Use : On Demand

Other Specifications

FDA : No Antistatic : No Antimicrobial : No